

19" Rack-mount 4U LCD Chassis

Gd YWjZwUhc b

- \$%) "G977 \ YUj mXi lmgHY`
Y`YWfcd`UHfX`Zcf`W Ugg]g`
- 8 Yg][bYX`VmiH`Y`c`W`UV`Y`Xccf`c`ZZ`cbh`
dUbY`Zcf`dfch`Wf]b[`H`Y`grghYa`gYW`f]mi`
- 8 Yg][bYX`H`Y`Ubh]j`jVfU]cb`WfX`WUa`d`
lc`_`YYd`H`Y`grghYa`gHUV`Y`UbX`gUZfmi`
- 5`i`a`]bi`a` \`UbX`Yg`
- Gi`ddcfh5H#5HL`Z`fa`a`cH`Yf`VcUfX`cf`
%`!`g`chVUW`d`UbY`
- 8]gd`UmfG<`!`%\$\$#`"(L`
 - TFT LCD 6.4" (640x480)
 - High brightness.(300 nit)
 - High colors.(262,144)
 - Analog VGA input
 - Built-in 5 languages OSD.
 - LCD On/off switch.
- 8]gd`UmfG<`!`%\$\$#`"(L`
 - TFT LCD 8.4" (800x600)
 - High colors.(262,144)
 - Analog VGA input
 - Built-in 5 languages OSD.
 - LCD On/off switch.
- 8]gd`UmfG<`!`%\$\$#`L`
 - TFT LCD 7" (800x480)
 - Analog VGA input
- 8f]j`Y6`Ung.`
 - 1 x 3.5" FDD
 - 2 x 5.25" CD-ROM
 - 3 x 3.5" HDD
- Dck`Yf`gi`dd`m`
 - PS/2 200W ~ 400W power supply
 - 250W ~ 600W ATX power supply



- 7`cc`]b[.
 - Built-in two 8cm cooling fans
 - Power supply fan
- CbY`_YmVcUfX`W`bbYwcf`]b`Z`cbhdUbY`
- @8`bX]WUcf. Power ON/OFF and Reset switches/ LED indicators at front panel
- GdYU`_Yf.`8`Ohm,0.4W`1.5"
- 7\`Ugg]g`7`c`c`fg.`Black and beige color available, OEM color welcome
- 8]ja`Ybg]cb.`
 - 483 (W) x 450 (D) x 177 (H) mm
 - N.W.: 13KGS, G.W.: 15KGS, CUFT: 3.3
- CdYfU]b[`HYa`dYfUi`fY.`0° ~ 50° C
- FYU]j`Y`<i`a`]X]m`5~85%
- C9A`GdYWjZwUhc`b`K`Y`W`a`Y`
- Cd]cb.`
 - Touch screen
 - Power supply



K-B; HCD'7 C'Z@H "

No. 9, Gong 6th Rd., Linkou Dist., New Taipei City 244, Taiwan (R. O. C.)
 TEL: 886 2 2601 9881(8686) FAX: 886 2 2601 3586(8229)
<http://www.wingtop.com.tw> E-mail:sales@wingtop.com.tw

May/29/2010