



IP-101 (1-Port KVM over IP)

The IP-101 is a control unit that allows access to computers, servers and KVM installations. IT offers platform independent, browser-based access from the LAN, WAN or Internet for up to 16 concurrent users. A total of 64 user accounts can be established with detailed permissions assigned to each. from one Local Console & one Remote Console (keyboard, monitor and mouse).

Features

Independent operation

Gives full control even during boot up, BIOS level or computer crash states. The IP-101 will work even if the controlled devices are not operational.

High video performance

The IP-101 can use a standard web browser but for superior graphical performance, Real VNC is used. Free of the limitations of HTTPS, Real VNC greatly enhances video performance.

Highly secure

Employing enterprise grade security (using AES 128 bit encryption and RSA 2048 bit public key authentication) as standard, the IP-101 is further enhanced by the use of Real VNC that allows for the creation of ciphered user communications.

User management

Knowing who does what and when is crucial for any remote access service. The IP-101 can create up to 16 user profiles with defined access rights.

Virtual media support

To transfer files from remote users to controlled computers, the IP-101 has been engineered to act as a conduit through which data can be passed. Files can be transferred via IP on to the IP-101 and on to the target computer by means of a USB virtual media port.



WINGTOP CO.,LTD.

No. 9, Kong 6Th Rd., 2nd Industry Park, Lin Kou, Taipei Hsien, Taiwan, R. O. C.
TEL: 886 2 2601 9881 (8686) FAX: 886 2 2601 3586(8229)
<http://www.wingtop.com.tw> E-mail:sales@wingtop.com.tw

Video resolutions: Supports standard PC, Sun and Mac video modes up to resolutions of 1600 x 1200 with scalable viewer

Hardware compatibility: Supports PC, RS/6000, Alpha, SGI computers, Sun and Mac. USB or PS/2 connections supported.

O/S compatibility: All known software and operating systems including Windows (all), DOS, Linux, Unix, BSD, Sun OS, Solaris, Mac OS, NetWare etc.

Specification

Function		Model No	IP-101
Computer Connections			1
Console Connectors	Keyboard		1 x USB & 1 x Mini Dim6
	Mouse		1 x USB & 1 x Mini Dim6
	Video		HDDB-15 male
KVM Connectors	KVM data		1 x HDDB-15 male
	LAN		1 x RJ-45 Female
	COM		1 x DB9 Male
	Link		1 x RJ-45 Female
	Power		1 x DC Jack
Video			1600 x 1200 DDC2B
Protocol Support			TCP/IP, HTTP, HTTPD, VDP, RADIUS, DHCP, SSL, ARP, DNS
Power Consumption			12V 0.5A
Environment	Operating Temp.		0°~50°C
	Storage Temp.		-20°~60°C
	Humidity		0~80% RH, Non-condensing
Physical Properties	Housing		Metal
	Weight		520 g (without cable)
	Dimensions		136.5x 110.5 x 27.5 (mm)
Built-in Cable			1 x 1.8M

* The specification and pictures are subject to change without notice.

* All trademarks and logos are the properties of their respective holders.



WINGTOP CO., LTD.

No. 9, Kong 6Th Rd., 2nd Industry Park, Lin Kou, Taipei Hsien, Taiwan, R. O. C.
 TEL: 886 2 2601 9881 (8686) FAX: 886 2 2601 3586(8229)
 http://www.wingtop.com.tw E-mail:sales@wingtop.com.tw