

19" Rack-mount 4U LCD Chassis

Specification

- 0.05" SECC heavy-duty steel electroplated for chassis
- Designed by the lockable door of front panel for protecting the system security
- Designed the anti-vibration card clamp to keep the system stable and safety
- Aluminum handles
- Support AT/ATX form mother board or 14-slot backplane
- Display:(SH-3100/6.4)
 - TFT LCD 6.4" (640x480)
 - High brightness.(300 nit)
 - High colors.(262,144)
 - Analog VGA input
 - Built-in 8 languages OSD.
 - LCD On/off switch.
- Display:(SH-3100/8.4)
 - TFT LCD 8.4" (800x600)
 - High colors.(262,144)
 - Analog VGA input
 - Built-in 8 languages OSD.
 - LCD On/off switch.
- Display:(SH-3100/7")
 - STN LCD 7" (640x480 mono)
 - With digital PCI/ISA expansion card
- Drive Bays:
 - 1 x 3.5" FDD
 - 2 x 5.25" CD-ROM
 - 3 x 3.5" HDD
- Power supply:
 - PS/2 250W ~ 400W power supply
 - 250W ~ 600W ATX power supply
- Cooling:
 - Built-in two 8cm cooling fans
 - Power supply fan
- One keyboard connector in front panel
- LED Indicator: Power ON/OFF and Reset switches/ LED indicators at front panel
- Speaker: 8 Ohm,0.4W 1.5"
- Chassis Colors: Black (beige color available, OEM color welcome)
- Dimension:
 - 483 (W) x 450 (D) x 177 (H) mm
 - N.W.: 13KGS, G.W.: 15KGS, CUFT: 3.3
- Operating Temperature: 0° ~ 50° C
- Relative Humidity: 5~85%
- OEM Specification Welcome
- Option:
 - Touch screen
 - PCI VGA CARD for TFT LCD (C&T 69000 Chip)



WINGTOP CO.,LTD.

No. 9, Kong 6Th Rd., 2nd Industry Park, Lin Kou, Taipei Hsien, Taiwan, R. O. C.

TEL: 886 2 2601 9881(8686) FAX: 886 2 2601 3586(8229)

<http://www.wingtop.com.tw> E-mail:sales@wingtop.com.tw

May/29/2003