

Specification

- **Designed for mountable industrial Panel PC**
- **Aluminum made front panel meet NEMA4/IP65 (optional)**
- **Processor:**
 - Socket 370 Supports Intel Pentium® III or other compatible processors (FC-PGA FC-PGA2) (CopperMine / Tualatin) Auto 66/75*/83*/100/112*/124*/133/140*/150* MHz FSB
- **15.0" TFT LCD Display:**
 - Resolutions 1024x768 (XGA)
 - Backlight MTBF: 50000 hours
 - Contrast ratio: 350:1
 - Brightness: 250 cd/m²
 - 500/1600 cd/m² brightness sunlight read-able (optional)
- **System Memory:**
 - 2x168-pin DIMM sockets
 - Supports PC-100 / PC-133 SDRAM and VCM SDRAM
 - Supports up to 1.0GB DRAM
 - Supports only 3.3V SDRAM DIMM
- **Expansion slot**
 - 3 x PCI slot
- **Driver Bay:**
 - 2 x 3.5" Remove-able driver bay
 - 1 x 5.25 Slim size CD-ROM
 - 1 x 3.5" FDD
- **Audio:** AC' 97 link controller
- **Ethernet:** 10/100bps fast Ethernet controller
- **I/O:**
 - 2 x Serial
 - 1 x Parallel
 - 2 x USB
 - 1 x RJ-45 LAN Jack
 - PS/2 Keyboard/mouse connector
 - 1 x Audio/game port
- **Power Supply**
 - DC Output rating: 250 W (300/350W optional)
 - Input voltage: 100~127/200~240VAC @ 47/63 Hz
 - MTBF: 80,000 hrs.
 - Safety: UL/ cUL/ TÜV/ FCC/ CE approved (PFC Optional)
- **Chassis Colors:** Black, OEM color welcome
- **Environment Specification**
 - Operating Temperature: 0° ~ 50° C (32 ~ 113° F)
 - Relative Humidity: 5~85%
- **OEM Specification Welcome**
- **Option**
 - Resistive touch screen (RS-232 / USB)
- **Dimensions**
 - W.430mm x H.285mm x D.175mm
 - N.W. 8.5 KGS, G.W. 10 KGS, CUFT. 2.7



WINGTOP CO.,LTD.

No. 9, Kong 6Th Rd., 2nd Industry Park, Lin Kou, Taipei Hsien, Taiwan, R. O. C.

TEL: 886 2 2601 9881 (8686)

FAX: 886 2 2601 3586 (8229)

<http://www.wingtop.com.tw>

E-mail:sales@wingtop.com.tw

May/29/2003